


JAMAK-C-HF C-PRO 8X(2+1)X0,5

Symmetrical halogen free data cable for industrial control equipment



GENERAL INFO

Product family description

Nominal voltage U [V]

These symmetrical data transmission cables are used in control and supervision centre for industrial sites. They are suitable for fixed installation inside housings.
50

CERTIFICATIONS AND DESIGN STANDARDS



EN 50575:2014/A1:2016
EN 60332-3

EN 60332-1-2

EN 61034-2

IEC 60754

CABLE DESIGN

Conductor material	Copper
Conductor surface	Tinned
Core insulation material	Polyethylene (PE)
Drain wire	Yes
Screen over stranding element	Foil
Screen over stranding	Foil
Material outer sheath	Thermoplastic polymer

APPLICATION PROPERTIES

Max. conductor temperature [°C]	70
Permitted cable outer temperature after assembling without vibration (min) [°C]	-30
Permitted cable outer temperature after assembling without vibration (max) [°C]	60
Permitted cable outer temperature during assembling/handling (min) [°C]	-5
Permitted cable outer temperature during assembling/handling (max) [°C]	40
Bending radius (rule)	15 x D under maximum tension 10 x D without tension

Reaction-to-fire class (acc. EN 13501-6)	Cca
Smoke development class (acc. EN 13501-6)	s1
Euro class flaming droplets/particles (acc. EN 13501-6)	d1
Euro class acidity (acc. EN 13501-6)	a1
Self-extinguishing	Yes
Flame retardant	In accordance with EN 13501-6
Halogen free (acc. IEC 60754-2)	Yes
Low smoke (acc. IEC 61034-2)	Yes

PROPERTIES

Product name	JAMAK-C-HF C-PRO 8X(2+1)X0,5
Diameter conductor [mm]	
Number of cores	16
Number of stranding elements	8
Nominal outer diameter [mm]	15
Cable weight [kg/km]	250
DOP number	1011735

Item name	EAN-code (GTIN)	Packaging type	Standard packaging quantity
JAMAK-C-HF C-PRO 8X(2+1)X0,5 MM2		Drum	1,000