



PRODUCT-DETAILS

EX63C20

Miniature Circuit Breaker - EX60 - 3P - 20 A - C



General Information	
Extended Product Type	EX63C20
Product ID	2CDS253087R0204
EAN	4053546091113
Catalog Description	Miniature Circuit Breaker - EX60 - 3P - 20 A - C
Long Description	EX63C20 Miniature Circuit Breaker AEG Redline 6kA, C-Characteristic 20A, 3P

Circular Value	
End Of Life Disassembling Instructions	9AKK108469A0853
Environmental Product Declaration - EPD	9AKK108469A0852

Technical	
Dielectric Test Voltage	50/60 Hz-1 min: 2 kV
Rated Ultimate Short-	10 kA

Circuit Breaking Capacity (I _{cu})	
Contact Position Indication	ON / OFF
Energy Limiting Class	3
Number of Protected Poles	3
Number of Poles	3P
Number of Modular Spacings per DIN Rail	3
Tightening Torque	2 N·m
Actuator Type	Toggle
Screw Terminal Type	Failsafe Biconnect Fork Bottom
Actuator Marking	Red ON / Green OFF
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Connecting Capacity	Busbar 10 ... 16 mm ² Busbar Fork 10 / 16mm ² mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 35 mm ² Rigid 0.75 ... 35 mm ² Solid 0.75 ... 35 mm ²
Wire Stripping Length	12.5 mm
Terminal Type	Screw Terminals

Electrical

Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 400 V AC
Operational Voltage	Maximum (Incl. Tolerance) 440 V AC
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V Phase to Phase 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Input Voltage Type	AC
Rated Current (I _n)	20 A
Rated Short-Circuit Capacity	6 kA (400 V AC) 6 kA
Rated Frequency (f)	50 / 60 Hz
Power Loss	at Rated Operating Conditions per Pole 2.5 W
Overvoltage Category	III

Design

Housing Material	Insulation Group II, RAL 7035
------------------	-------------------------------

Material Compliance

REACH Information	False - does not contain substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Degree of Protection	IP20 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms

Dimensions

Width in Number of Modular Spacings	3.0
Product Net Width	53 mm
Product Net Height	88 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.375 kg
Pole Net Weight	0.125 kg
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	0.4 kg

Installation

Instructions and Manuals	9AKK108468A7757
Mounting Type	DIN-Rail
Mounting Position	any

External Classifications and Standards

ETIM 9	EC000042 - Miniature circuit breaker (MCB)
ETIM 10	EC000042 - Miniature circuit breaker (MCB)
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4897 >> Miniature circuit breakers
Standards	IEC/EN 60898-1

Categories

Madalpingetooted ja süsteemid → DIN-lati moodulaparaadid → AEG → Miniature Circuit Breakers MCBs

