

137.3311P

SP BELL PUSH SWITCH "PRESS"
SP BELL PUSH SWITCH "PRESS"
Marked "PRESS" 10A M95(95x95mm)



EN 60669-1 (1999)
EN 60669-1/A1 (2002)
EN 60669-1/A2 (2008)
IEC 60669-1 (2007)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

Commercial Series

PROTECTA Series

Synthetical description

SP BELL PUSH SWITCH "PRESS"

Mounting version

FLUSH MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current

10A

Rated voltage

250V

■ PHYSICAL CHARACTERISTICS

Mounting version

FLUSH MOUNTING

Protection degree

Splash proof

Protection degree IP

IP66

Material

THERMOPLASTIC

Working temperature

-20°C/+60°C

Protection degree IK

IK07

Warning light

WITH NEON

Pictogram

Marked "PRESS"

■ DIMENSIONAL CHARACTERISTICS

N.° modules

1 GANG

Dimensions

M95(95x95mm)

■ DOWNLOAD[Technical drawing \[PDF\]](#)[Technical drawing \[DWG\]](#)[Technical drawing \[STP\]](#)[Instruction manual](#)**■ OPTIONS & VARIOUS NOTES**

Catalogue notes

Flush mounting: box not included.