

YG2A14-030UB3XLEAX

Sensor/actuator cable





Ordering information

Туре	Part no.
YG2A14-030UB3XLEAX	2105351

Other models and accessories → www.sick.com/Sensor_actuator_cable



Detailed technical data

Technical specifications

reenmear opeemearene	
Connection type head A	Female connector, M12, 4-pin, angled, A-coded
Connection type head B	Flying leads
Locking plug connector	Screw connection
Connector material	TPU
Connector color	Black
Locking nut material	Zinc die-cast, nickel-plated
Seal material	FKM
Tightening torque	0.6 Nm
Width across flats	13
Cable	3 m, 4-wire, PUR, halogen-free
Jacket material	PUR, halogen-free
Jacket color	Black
Cable diameter	4.5 mm
Conductor cross section	0.34 mm ²
Shielding	Unshielded
Bending radius	
Flexible use	> 10 x cable diameter
Stationary position	> 5 x cable diameter
Drag chain operation	> 10 x cable diameter
Bending cycles	10,000,000
Nominal voltage, cable	300 V AC
Test voltage, cable	2,500 V AC
Reference voltage	
	250 V AC
	250 V DC
Rated impulse voltage	2.5 kV
Current loading	4 A
Traversing speed	3 m/s


Torsion force Torsion cycles Cycles per minutes Application Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation CE UL UL File No. Ea335179 Enclosure rating Operating temperature Flexible use Stationary position Drag chain operation Drag chain operation Plexible use Stationary position Head Drag chain operation Authorizations Flexible use Stationary position Head Drag chain operation Head Drag chain operation Head Drag chain operation Head III		
Sensor/actuator cable	Travelling distance	10 m
Torsion force 180° / 1 m Torsion cycles 2,000,000 Cycles per minutes 35 Application Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation Eight P65 / IP66K / IP67 Operating temperature Flexible use Stationary position Drag chain operation Flexible use -25°C+80°C -40°C+80°C -25°C+80°C	Acceleration	≤ 10 m/s²
Torsion cycles 2,000,000 Cycles per minutes Application Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation CE UL UL File No. E335179 Enclosure rating Operating temperature Flexible use Stationary position Drag chain operation Contamination rating Insulation resistance Overvoltage category Thermal resistance, piping 100 MΩ Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation CE UL UL E35179 E135179 E13	Signal type	Sensor/actuator cable
Cycles per minutes Application Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation CE UL UL File No. E335179 Enclosure rating Operating temperature Flexible use Stationary position Drag chain operation Drag chain operation Head Contamination rating Insulation resistance Overvoltage category Thermal resistance, piping Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation E35 CE UL L335179 L965 / IP66K / IP67 CE UL L335179 L965 / IP66K / IP67 CE UL L335179 L965 / IP66K / IP67 COL +80 ° C -40 ° C +80 ° C -25 ° C +80 ° C -25 ° C +85 ° C Contamination rating Insulation resistance 100 MΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Torsion force	180° / 1 m
Application Uncontaminated zones Zones with oils and lubricants Robot Drag chain operation Authorizations CE UL UL File No. E335179 Enclosure rating IP65 / IP66K / IP67 Operating temperature Flexible use Stationary position -40 °C +80 °C -40 °C +80 °C -25 °C +80 °C -25 °C +80 °C -25 °C +85 °C Contamination rating Insulation resistance 3 Insulation resistance Query III 100 MΩ Specific insulation resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Torsion cycles	2,000,000
Zones with oils and lubricants Robot Drag chain operation CE UL UL File No. E335179 Enclosure rating IP65 / IP66K / IP67 Operating temperature Flexible use -25 °C +80 °C -40 °C +80 °C -25 °C +80 °C Drag chain operation -25 °C +80 °C -25 °C +85 °C Contamination rating 3 Insulation resistance 100 MΩ Overvoltage category III Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Cycles per minutes	35
UL File No. E335179 Enclosure rating IP65 / IP66K / IP67 Operating temperature Flexible use	Application	Zones with oils and lubricants Robot
Enclosure rating IP65 / IP66K / IP67 Operating temperature Flexible use -25 °C +80 °C Stationary position -40 °C +80 °C Drag chain operation -25 °C +80 °C Head -25 °C +85 °C Contamination rating 3 Insulation resistance 100 MΩ Overvoltage category III Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Authorizations	
Operating temperature Flexible use -25 °C +80 °C Stationary position -40 °C +80 °C -25 °C +80 °C -25 °C +85 °C Contamination rating 3 Insulation resistance 100 MΩ Overvoltage category III Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	UL File No.	E335179
Flexible use Stationary position Drag chain operation Head Contamination rating Insulation resistance Overvoltage category Thermal resistance, piping Flexible use -25 °C +80 °C -40 °C +80 °C -25 °C +85 °C 25 °C +85 °C 100 MΩ 100 MΩ Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Enclosure rating	IP65 / IP66K / IP67
Stationary position Drag chain operation Head Contamination rating Insulation resistance Overvoltage category Thermal resistance, piping -40 °C +80 °C -25 °C +80 °C -25 °C +85 °C 3 Insulation resistance 100 MΩ III Specific insulation resistance 30 mΩ Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Operating temperature	
Drag chain operation Head -25 °C +80 °C -25 °C +85 °C Contamination rating 3 Insulation resistance 100 MΩ Overvoltage category III Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Flexible use	-25 °C +80 °C
Head -25 °C +85 °C Contamination rating 3 Insulation resistance 100 MΩ Overvoltage category III Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Stationary position	-40 °C +80 °C
Contamination rating 3 Insulation resistance 100 MΩ Overvoltage category III Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Drag chain operation	-25 °C +80 °C
Insulation resistance $100 \text{ M}\Omega$ Overvoltage category III Specific insulation resistance $30 \text{ m}\Omega$ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Head	-25 °C +85 °C
Overvoltage category III Specific insulation resistance $30 \text{ m}\Omega$ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Contamination rating	3
Specific insulation resistance 30 mΩ Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Insulation resistance	100 ΜΩ
Thermal resistance, piping Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1,	Overvoltage category	III
	Specific insulation resistance	30 mΩ
	Thermal resistance, piping	

Classifications

ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

YG2A14-030UB3XLEAX | Sensor/actuator cable

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

