

Luppa

Luppa CCT Multi Wattage Black Code: ALUP/1/B







Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Outdoor, Retail	
Specification	Performance	



PRODUCT FEATURES

- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for education, commercial and industrial applications
- Integrated switch on the LED board allows for the section behind the eyelid to be deactivated, improving energy efficiency when using the eyelid trim
- Tamper-proof stainless steel allen key screws

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Gear tray located on the diffuser, allowing the base to be installed and then the diffuser connected, this coupled with removeable conduit entries on base ensure a quick and simple installation
- Non-dimmable

GENER	AL INFORMATION
Wattage	16W - 23W
Lumens Delivered	2100lm - 3200lm (4000K)
Lm/W	135lm/W - 140lm/W (4000K)
Beam Angle	107
CRI	80
ССТ	3000/4000K
Input	220-240V
Operating Temp	-20°C to 40°C
SDCM	5
UGR	25
Product Weight without Packaging	2 kg

TECHNIC	CAL INFORMATION	
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP66	
IK Rating	IK08	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Surface, Wall	
Lumen Depreciation	L80 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	298 mm	

Belfast: +44 (0) 2890 773750 Warrington: +44 (0) 1942 433333 ansell_lightingAnsell Lighting

f anselllighting
ansell_lighting





Application	ication Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Outdoor, Retail	
Specification	Performance	

Luppa

Luppa CCT Multi Wattage Black Code: ALUP/1/B







