

Product sheet



DPX³ 1600 LEGRAND

Earth leakage module 4 poles, with rated current of 630A, for DPX³ 630 circuit breaker

REF. 026065 | EAN. 3245060260651

DPX³, auxiliary for moulded case circuit breaker and trip-free switch

> [Visit e-catalogue](#)

Description

DPX³, auxiliary for moulded case circuit breaker and trip-free switch

Product charateristics

- Can be fitted onto DPX³ 630 and DPX³-I 630
- Adjustable, sealable sensitivity: 0.03 - 0.3 - 1 - 3 A.
Adjustable time delay: 0 - 0.3 - 1 - 3 s
- Equipped with: test push-button and reset push-button.
- 230V~ to 500 V~
- Mounted underneath

Installation

- Switch for mechanical tests (installation insulation test)

Usage

- Remote earth fault signalling contact.

Technical characteristics

Nominal voltage	230-500 V
Nominal current	630 A
Rated fault current adjustable	Yes
Rated fault current	0.03-3 A

Max. delay time	3000 ms
Delay adjustable	Yes
Number of poles	4
Leakage current type	A

Documentation

TECHNICAL DOCUMENTATION

- Technical Guide: Coordination between protection devices | PDF (5.41Mo)
- Workshop Book: DPX³ 125HP/160HP/250HP/630/1600 | PDF (239.04Mo)
- LE07066AC.pdf | PDF (0.92Mo)
- Cahier d'atelier : DPX³ 125HP/160HP/250HP/630/1600 | PDF (239.32Mo)

CATALOGUE PAGE & OTHERS

- ex223001_0179.pdf | PDF (0.08Mo)

CAD & Design specs / BIM

 026065.dwg | DWG (0.15Mo)

Agreements & Certificates

 CCC-2005010307161816 | (4.86Mo)