

Product sheet



LEGRAND

2P+E schuko 2 modules inclined 45 mat black

REF. 079355L | EAN. 3414971637986

> [Visit e-catalogue](#)

Technical characteristics

Model	Socket outlet with protective contact CEE 7/3 (type F)
Concurrently switching neutral conductor	No
Protective contact	Other
Number of active contacts (round)	2
Number of active contacts (flat)	0
Number of active contacts (square)	0
Assembly arrangement	Basic element with central cover plate
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	1
Socket outlets phase-separated	No
Number of modules (module system)	2
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	None
Connection type	Push-in clamp
With hinged lid	No

Halogen free	Yes
Surface protection	Lacquered
Surface finishing	Matt
Antimicrobial treatment	No
With loop through function	No
With on/off switch	No
Colour of switch operator	Black
Rotated central insert	Yes
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Device width	45 mm
Device height	45 mm
Device depth	43 mm
Min. depth of built-in installation box	40 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No

With enhanced contact protection	Yes
Label space/information surface	No
Colour	Black
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Snap mounting (engagement)
Material	Plastic
Material quality	Thermoplastic

IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	34.5 mm
Operating / setting temperature	-5-35 °C
Storage temperature	-10-70 °C
Voltage type	AC
Power Delivery	No
Terminal marking indication	Yes
Prewired	Yes
Terminals capacity	2.5-2.5 mm ²
Cable nature for connection	Flexible or rigid
Cable section	2.5-2.5 mm ²
Cable support	Other
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

-  F00754FR-10.pdf | PDF (0.54Mo)
-  F00754EN-10.pdf | PDF (0.54Mo)

Agreements & Certificates

-  VDE-40036340 | (0.39Mo)
-  OC / CB-HU-005369 | (0.78Mo)
-  VDE-40036340 | (0.29Mo)
-  OC / CB-HU-003962 | (0.48Mo)
-  AENOR-030/002523 | (0.42Mo)

CATALOGUE PAGE & OTHERS

-  ex223001_1129.pdf | PDF (0.1Mo)
-  ex223001_1182.pdf | PDF (0.11Mo)