




PRODUCT-DETAILS

VEM4

VEM4 Mechanical and Electrical Interlock Set



General Information	
Extended Product Type	VEM4
Product ID	1SBN030111R1000
EAN	3471523130616
Catalog Description	VEM4 Mechanical and Electrical Interlock Set
Long Description	VEM4 is a mechanical and electrical interlock set for the interlocking side-by-side without additional width of two AF09 ... AF38 or AFC09 ... AFC38 contactors. VEM4 set includes a mechanical interlock unit VM4 with 2 fixing clips (BB4) and a VE4 electrical interlock block with A2-A2 connection. Fixing the electrical interlock block on the front of the contactors connects the 2 built-in N.C. interlocking contacts to the two coils saving up to 50% less wiring compared to conventional electrical interlocking. VE4 block must be used with A2-A2 connection to respect the electrical connection diagram.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical Information	1SBC100214C0202
Instructions and Manuals	1SBC101028M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	25 mm
Product Net Depth / Length	31.6 mm
Product Net Height	43 mm
Product Net Weight	0.035 kg

Technical

Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	2
Number of Poles	2P
Standards	IEC/EN 60947-5-1, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60947-1-13, CSA C22.2 No. 60947-4-1
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 690 V
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Maximum Electrical Switching Frequency	1200 cycles per hour
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	1800 cycles per hour
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 10 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Tightening Torque	Auxiliary Circuit 1.2 N·m
Terminal Type	Screw Terminals
Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38

AF38Z
AFC09
AFC12
AFC16
AFC26
AFC30
AFC38
AF09B
AF09ZB
AF12B
AF12ZB
AF16B
AF16ZB
AF26B
AF26ZB
AF30B
AF30ZB
AF38B
AF38ZB

Product Name	Mechanical and Electrical Interlock Set
--------------	---

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 500 V AC/DC
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

ABS Certificate	ABS_20-2060694-PDA
CB Certificate	CB_SE-112440
CCC Certificate	CCC_2024010305648906
Declaration of Conformity - CCC	2020980304001259
Declaration of Conformity - CE	1SBD250007U1000
Declaration of Conformity - UKCA	1SBD250038U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
RINA Certificate	RINA_ELE084013XG
UL Certificate	UL-US-2017443-2 UL-CA-2013922-2
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	92 mm
Package Level 1 Depth / Length	35 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.035 kg
Package Level 1 EAN	3471523130616
Package Level 2 Units	box 132 piece
Package Level 2 Gross Weight	4.62 kg

External Classifications and Standards

ETIM 7	EC001044 - Mechanic interlock for switch
ETIM 8	EC001044 - Mechanic interlock for switch
ETIM 9	EC001044 - Mechanic interlock for switch
eClass	V11.0 : 27371303
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	3706551
E-Number (Sweden)	3210004

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

