

Product Information

95 05 20 SB

Angled Electricians' Shears



MM ∡45°

- Precision-ground blades with fine serrations for a clean, non-slip cut
- Adapted to the hand: angled blades and optimised handle design for improved ergonomics
- Two crimping areas for wire ferrules of 0.5 6 mm² and 10 25 mm²
- Suitable for cutting of the following cables: 1 x 25 mm² such as H01 N2-D flexible / stranded rubber connecting and control cables for arc welding, 5 x 2.5 mm² such as H07 RN-F flexible and stranded heavy rubber hose line cable, flexible and stranded cables up to Ø 15 mm, 5 x 1.5 mm² such as damp-proof installation cables
- Includes opening spring and lock for easy storage
- Tether attachment point can be used with KNIPEX Tethered Tools System
- Cutting edges made from stainless steel, hardness of cutting edges 56 HRC
- Not suitable for cutting solid conductors
- Practical belt pouch (00 19 75 LE) available separately

General	
Part No.	95 05 20 SB
EAN	4003773082699
Shears	mirror polished
Handles	with multi-component grips, glass fibre reinforced plastic
Weight	190 g
Dimensions	180 x 76 x 21 mm
REACH compliant	does not contain SVHC
RoHS compliant	not applicable


Technical changes and errors excepted















KNIPEX Quality















KNIPEX Quality





