



Slim Panel Basic G4

- Cost effective LED Slim Panel family, including versions suitable for offices (UGR < 19)
- Improved efficacy up to 130lm/W
- Replacement for conventional 4x18W or 2x36W luminaire
- Recessed ceiling frame and surface module kit available as accessory
- Suitable for recessed and suspended applications



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen (lm)	Efficacy (lm/W)	UGR CCT (K)	Net Weight (kg/pc)
On-Off/PIR sensor							
542016020500	LEDPanelS-B4 Sq595-23/34W-830-U19-PIR	TL 4x18W	23 - 34	2990 - 4420	130	19 3000	2

Available on request with Wieland GST18 or WAGO WINSTA connector, or Euro/Schuko plug. DALI2 versions are compatible with central emergency lighting according to EN 50172.
A PIR sensor panel can control up to 4 additional panels

Accessories

Recessed Mounting Frame



542098009600
LEDPanelRc Sq600-Frame-WH



140060852
LEDFixture-Ceiling-Cable-Kit-0.5m



542003021800
LEDPanelRc-S-B2 Mounting-Springs



542098045500
LEDPanelS-P Suspension-Kit-G6

Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
542016020500	LEDPanelS-B4 Sq595-23/34W-830-U19-PIR	94051190	605x75x610	2.78	6937209604521	1
140060852	LEDFixture-Ceiling-Cable-Kit-0.5m	73121020	510x100x11	0.40	6956321895266	1
542003021800	LEDPanelRc-S-B2 Mounting-Springs	73209090	280x200x170	0.10	6941408821672	1
542098000900	LEDPanelRC-SI U19 EM-kit 3h	85044083	490x390x150	1.08	6941497702333	1
542098009600	LEDPanelRc Sq600-Frame-WH	94059900	688x694x88	1.79	6941497704061	1
542098030700	Junction-Box-WH	85369010	44x104x36	0.06	6941408868684	1
542098045500	LEDPanelS-P Suspension-Kit-G6	73121020	61x130x130	0.22	6941497784773	1

Technical Specifications

Lifetime (L70)	70,000 h
Lifetime (L80)	50,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	3
Dimmability	Sensor controlled (MD)
Finishing	White RAL9003
RAL-Number	9003
Colour rendering index (CRI)	> 80
Impact strength (IK)	IK03
Protection class	II
Risk group (EN 62471)	RG0
With control gear	True
Glow wire test	650 °C
Driver failure rate (at 5,000 hrs)	≤ 1 %
Power factor	≥ 0.9

Electrical Supply


Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	See catalogue appendix Connection Specifications

Mechanical Properties

Housing material	Aluminium
Cover material	Polystyrene

Ambient Conditions

Operating temperature	-10 ~ 45 °C
Operating temperature (MD)	-10 ~ 45 °C
Application temperature	25 °C




Dimensional Drawing (mm)



Type	A	B	C
Re295	1195	295	32




Type	A	B	C
Sq595	595	595	32
Sq620	620	620	34



Type	A	B	C
Sq595	595	595	67
Sq620	620	620	67

Motion Sensors



Photometric Data



• Connection kit, accessory product for Tablet

Packaging information

Item Code	Item Description	ETN Code	Dimensions (mm) (LxWxH)	Items Weight (kg)	EAN	Qty/Box
52408602000	1027 Tablet P Connection Kit	9420592	Pho2x1x31	0.15	494249773377	1
Technical Specifications						
Colour	Black	Diameter	- mm			
Width	20 mm	Length	32 mm			
Height	10.1 mm	Material	Aluminium			
Type of accessory/spare part	Cable/connector straight					

Version August 2025
Data subject to change

Check our website for more detailed product specifications.