



Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Vantage UGR<19

Vantage 2 UGR19 CCT Downlight

Code: AVLG2/1



PRODUCT FEATURES

- Performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Downlight design allows installation into existing hole cut-outs from 68mm, 100mm, 150mm and 200mm
- Deep cut-off angle for glare control and comfort
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire

GENERAL INFORMATION	
Wattage	8.5W - 12W
Lumens Delivered	980lm - 1400lm (4000K)
Lm/W	117lm/W
Beam Angle	36
CRI	80
CCT	3000K-4000K-6500K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	6
UGR	13
Cut-Out Size	100
Product Weight without Packaging	0.21 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 100,000
Warranty (Years)	5
CE Mark	Yes
Diameter	118 mm
Height	68 mm



Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Vantage UGR<19

Vantage 2 UGR19 CCT Downlight

Code: AVLG2/1

