

Product sheet



PLEXO™ LEGRAND

Plexo™ - German standard socket outlet with screw terminals - Grey - surface

REF. 069733L | EAN. 3414971882133

[> Visit e-catalogue](#)

Technical characteristics

Model	Socket outlet with protective contact CEE 7/3 (type F)
Concurrently switching neutral conductor	No
Protective contact	Other
Number of active contacts (round)	2
Number of active contacts (flat)	0
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	1
Socket outlets phase-separated	No
Number of modules (module system)	2
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	Degree of protection (IP)
Connection type	Screwed terminal
With hinged lid	Yes

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Matt
Antimicrobial treatment	No
With loop through function	No
With on/off switch	No
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP55
degree of impact strength (IK)	IK08
Device width	82 mm
Device height	85 mm
Device depth	62 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No

With enhanced contact protection	Yes
Label space/information surface	No
Colour	Grey
RAL-number (similar)	7046
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Surface mounted
Type of fastening	Mounting with screw

IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	Yes
Operating / setting temperature (Min-Max)	-10-40 °C
Storage temperature (Min-Max)	-25-60 °C
Voltage type	AC
Terminal marking indication	Yes
Prewired	No
Terminals capacity (Min-Max)	1.5-2.5 mm ²
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	1.5-2.5 mm ²
Tube diameter for wall mounted product (Min-Max)	16-25 mm
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F03972EN-00.pdf | PDF (0.96Mo)

F03972FR-00.pdf | PDF (0.96Mo)

F04054EN-00.pdf | PDF (0.96Mo)

CAD & Design specs / BIM

3D_LG-069733L.stp | IFC (2.25Mo)

BIM-LEGRAND-PLEXO-2025-FRANCAIS.rvt | RVT (135.87Mo)

BIM-LEGRAND-PLEXO-2025-ENGLISH.rvt | RVT (137.72Mo)

CATALOGUE PAGE & OTHERS

ex223001_0790.pdf | PDF (0.11Mo)

Agreements & Certificates

MEEI-UP 69267307 003 | (1.57Mo)

MEEI-UP 69267307 002 | (1.25Mo)

SNI-PCS 01600.01 | (2.26Mo)

OC / CB-FR_718712/M1 | (0.82Mo)

KSC-JW04001-24002 | (4.69Mo)

MEEI-UP 69267307 001 | (1.57Mo)

AENOR-030/002645 | (0.89Mo)

LGRP-01918-V01.01-EN.pdf | PDF (0.87Mo)