

Product data sheet



CÉLIANE LEGRAND

2P+E SCHUKO SOCKET OUTLET AUTOMATIC TERMINAL

REF. LG-CM0120 | EAN. 3414972421683

[> The product details page](#)

Tehnilised omadused

| | |
|---|--|
| Model | Socket outlet with protective contact CEE 7/3 (type F) |
| Concurrently switching neutral conductor | No |
| Protective contact | Other |
| Number of active contacts (round) | 2 |
| Number of active contacts (flat) | 0 |
| Number of active contacts (square) | 0 |
| Assembly arrangement | Basic element |
| With complementary luminous signal | No |
| Number of ports USB-A | 0 |
| Number of ports USB-C | 0 |
| Number of socket outlets | 1 |
| Socket outlets phase-separated | No |
| Number of modules (module system) | 2 |
| Number of socket outlets switchable | 0 |
| Number of phases | 1 |
| Imprint/indication | None |
| Connection type | Push-in clamp |
| With hinged lid | No |
| With enhanced contact protection | Yes |

| | |
|--|-----------|
| Halogen free | Yes |
| Surface protection | Untreated |
| Surface finishing | Matt |
| Antimicrobial treatment | No |
| With loop through function | Yes |
| With on/off switch | No |
| Rotated central insert | No |
| Nominal current | 16 A |
| Nominal voltage | 250 V |
| Frequency (Min-Max) | 50-60 Hz |
| Suitable for degree of protection (IP) | IP20 |
| degree of impact strength (IK) | IK04 |
| Device width | 45 mm |
| Device height | 45 mm |
| Device depth | 40 mm |
| Min. depth of built-in installation box | 40 mm |
| Compatible with Apple HomeKit | No |
| Compatible with Amazon Alexa | No |
| Compatible with Google Assistant | No |
| IFTTT support available | No |

| | |
|---------------------------------|----------------------------|
| Label space/information surface | No |
| Colour | Other |
| Metallic colour | No |
| Transparent | No |
| Lockable | No |
| Eject-mechanism | No |
| Insulated mounting | No |
| With function lighting | No |
| With orientation lighting | No |
| Overvoltage protection | No |
| Fault current protection | No |
| With miniature fuse | No |
| Special power supply | None |
| Mounting method | Module frame |
| Type of fastening | Snap mounting (engagement) |
| Material | Plastic |
| Material quality | Thermoplastic |

| | |
|---|-------------------------|
| With Wi-Fi signal repeater | No |
| With built-in bluetooth speaker | No |
| For heavy conditions according to VDE | No |
| Built-in depth | 34.5 mm |
| Operating / setting temperature (Min-Max) | -5-50 °C |
| Storage temperature (Min-Max) | -10-70 °C |
| Voltage type | AC |
| Power Delivery | No |
| Terminal marking indication | Yes |
| Prewired | No |
| Terminals capacity (Min-Max) | 1.5-2.5 mm ² |
| Cable nature for connection | Flexible or rigid |
| Cable section (Min-Max) | 1.5-2.5 mm ² |
| Cable support | Other |
| Connected object | No |

Dokumentatsioon

Tehniline dokumentatsioon

→ [F04009EN-00.pdf](#) | PDF (0.85Mo)

CAD & Disaini spetsifikatsioonid / BIM

→ [3D_LG-CM0120.stp](#) | IFC (4.67Mo)

Regulated Substances Compliance

[RoHS Certificate of Compliance](#) | PDF

Lepingud ja sertifikaadid

→ [OC / CB-HU-005377](#) | (0.56Mo)

→ [MEEI-UP 69267544 002](#) | (1.23Mo)

→ [LGRP-02141-V01.01-EN.pdf](#) | PDF (0.85Mo)