




PRODUCT-DETAILS

20 EUCB2USBAC-914

SCHUKO® USB socket insert Safety Shutter with USB A/C alpine white - Busch-balance SI



General Information	
Extended Product Type:	20 EUCB2USBAC-914
Product ID:	2CKA002011A6298
EAN:	4011395329153
Catalog Description:	SCHUKO® USB socket insert Safety Shutter with USB A/C alpine white - Busch-balance SI
Long Description:	SCHUKO®/USB A&C socket outlet With screwless terminals. For connecting electric loads. For supply and support of mobile devices via USB-cable. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet. With 1x USB type A and 1x USB type C outputs. Support of loading protocol on the USB-A connection: Apple MFI with 2.4 A and BC 1.2 with 1.5 A. Support of loading protocol on the USB-C connection: USB-PD till 3 A, Apple MFI till 2.4 A and BC 1.2 with 1.5 A. With electronic short-circuit protection. With electronic overload protection. USB-A port: Max. current 2.4 A. USB-C port: Max. current 3 A* *3 A requires approved charging cables. No data transfer between USB ports. Use dust cover 2098 for USB-A port when cleaning the device.

Display Name: 20 EUCB2USBAC-914

Installation

Instructions and Manuals:	2CKA000073B5395
Mounting Type:	Flush Mounted
Type of Fastening:	Mounting with Claw Mounting with Screw
Modular Components Included:	Cover with Flush Mounted Insert and Mounting Plate

Environmental

Ambient Air Temperature:	Operation 5 ... +35 °C
Degree of Protection:	IP20

Technical

Function:	USB with enhanced contact protection
Number of Poles:	2P+PE
Number of Phases:	1-phase
Number of Outputs:	USB-A 1 USB-C 1
Connection Type:	USB
Socket Outlet Type:	Protective Contact (SCHUKO)
Options Available:	with USB A/C, Safety Shutter
Terminal Type:	Screwless Terminals
Safety Function Option:	Safety Shutter
USB Port Type:	USB A/C
Charging Protocol:	Apple MFi 2.4 A BC 1.2 DCP USB PD 3.0

Electrical

Rated Voltage (U _r):	230 V
Secondary Voltage:	5 V
Rated Current (I _n):	16 A
Rated Frequency (f):	50/60 Hz
Power Loss:	0.075 W
Power Watt:	Maximum DC 15 W

Design

Design Range:	Busch-balance SI
Surface Finishing:	Untreated Glossy
Material:	Thermoplastic
Label Space Provided:	Without Label Space
RAL Number:	Similar to RAL 9010
Color:	alpine white
Number of Gangs:	1-gang

Dimensions

Product Net Width:	71 mm
Product Net Height:	71 mm
Product Net Depth / Length:	58 mm
Product Net Weight:	117.5 g
Built-In Depth (t₂):	39.5 mm
Dimension Diagram:	2CKA000097E4057

Ordering

Replaced Product ID (OLD):	2CKA002011A6266
-----------------------------------	-----------------

Material Compliance

RoHS Declaration:	2CKA200000E7797
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration:	2CKA309999E9999
REACH Information:	True - contains substances > 0.1 mass percentage
REACH Date:	20260216
Conflict Minerals Reporting Template (CMRT):	9AKK108468A3363
SCIP:	67ce09d1-8092-4d91-91dd-96d7c409e963 Germany
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B:	Business To Consumer

Certificates and Declarations

Declaration of Conformity - CE:	2CKA100000E4815
EU Data Act Applicability and Compliance:	Not Applicable

External Classifications and Standards	
ETIM 9:	EC000125 - Socket outlet
ETIM 10:	EC000125 - Socket outlet
eClass:	V11.0 : 27144042

Categories

Products > Low Voltage Products and Systems > Wiring Accessories - Electronic Devices > USB Chargers > Socket Outlets with USB

Products > Low Voltage Products and Systems > Wiring Accessories - Light Switch Ranges > Cover Plates and Control Elements > Socket Outlets

