



PRODUCT-DETAILS

CE5-01D0.1

CE5-01D0.1 Auxiliary Contact Block



General Information	
Extended Product Type:	CE5-01D0.1
Product ID:	1SBN010015R1001
EAN:	3471522199140
Catalog Description:	CE5-01D0.1 Auxiliary Contact Block
Long Description:	CE5-01D0.1 is a 1-pole front mounted auxiliary contact block equipped with screw terminals and can be fitted on AF09(Z)...96, A9...75, AFC09...38, AL9...AE75, AX9...AX80 contactors and NF(C)(Z), N, NL, NX contactor relays. CE5-01D0.1 is used for the operation of auxiliary circuits and control circuits for severe industrial environments. CE5-01D0.1 is available with 1 N.C. including a built-in microswitch IP40, degree of protection (IP20 on terminals), defined for a 0.1 A AC-14 24-127 V 50/60 Hz / DC-12 24-110 V DC.
Display Name:	CE5-01D0.1

Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Popular Downloads

Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101013M5501
Instructions and Manuals (Part 2):	1SAC200017M0002
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	9.8 mm
Product Net Depth / Length:	32.5 mm
Product Net Height:	46.8 mm
Product Net Weight:	0.02 kg

Technical

Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	1
Number of Poles:	1P
Standards:	IEC/EN 60947-5-1
Rated Operational Voltage:	Auxiliary Circuit 125 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I_e):	(24 / 127 V) 0.1 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 250 V
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 4 mm ²
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40
Tightening Torque:	Auxiliary Circuit 1 N·m
Terminal Type:	Screw Terminals
Suitable For:	AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38 AF38Z AF40 AF52 AF65 AF80 AF96 AFC09 AFC12 AFC16 AFC26 AFC30 AFC38

NF22E
NFZ22E
NF31E
NFZ31E
NF40E
NFZ40E
NFC22E
NFC31E
NFC40E
A9
A12
A16
A26
A30
A40
A50
A63
A75
A95
A110
AL9
AL9Z
AL12
AL12Z
AL16
AL16Z
AL26
AL30
AL40
AE45
AE50
AE63
AE75
N22E
N31E
N40E
NL31E
NLZ31E
NL40E
NLZ40E
AX06
AX09
AX12
AX18
AX25
AX32
AX40
AX50
AX65
AX80
NX22E
NX31E
NX40E

Product Name:	Auxiliary Contact Block
---------------	-------------------------

Material Compliance	
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate:	CB_SE-94569
CQC Certificate:	CQC2011010304466171
Declaration of Conformity - CCC:	2020980304001286
Declaration of Conformity - CE:	1SBD250817U1000
Declaration of Conformity - UKCA:	1SBD250834U1000
RINA Certificate:	RINA_ELE172319XG001

Container Information

Package Level 1 Units:	blister 1 piece
Package Level 1 Width:	100 mm
Package Level 1 Depth / Length:	100 mm
Package Level 1 Height:	10 mm
Package Level 1 Gross Weight:	0.02 kg
Package Level 1 EAN:	3471522199140

External Classifications and Standards

Object Classification Code:	K
ETIM 7:	EC000041 - Auxiliary contact block
ETIM 8:	EC000041 - Auxiliary contact block
ETIM 9:	EC000041 - Auxiliary contact block
eClass:	V11.0 : 27371302
UNSPSC:	39121522
IDEA Granular Category Code (IGCC):	4743 >> Auxiliary contact block
E-Number (Finland):	3709157

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors

