



DATA SHEET

# IME08-04NPOZT0K

IME  
Inductive proximity sensors

# SICK

Sensor Intelligence



Illustration may differ

INDUCTIVE PROXIMITY SENSORS

IME08-04NPOZT0K

ORDERING INFORMATION

| Type            | part no. |
|-----------------|----------|
| IME08-04NPOZT0K | 1040889  |

Further device versions and accessories at [www.sick.com/IME](http://www.sick.com/IME)



DETAILED TECHNICAL DATA

FEATURES

|                          |                                          |
|--------------------------|------------------------------------------|
| Housing                  | Metric                                   |
| Housing                  | Short-body                               |
| Thread size              | M8 x 1                                   |
| Diameter                 | Ø 8 mm                                   |
| Sensing range $S_n$      | 4 mm                                     |
| Safe sensing range $S_a$ | 3.24 mm                                  |
| Installation type        | Non-flush                                |
| Switching frequency      | 4,000 Hz                                 |
| Connection type          | Connector M8, 3-pin                      |
| Switching output         | PNP                                      |
| Switching output detail  | PNP                                      |
| Output function          | NC                                       |
| Electrical wiring        | DC 3-wire                                |
| Enclosure rating         | IP67 <sup>1)</sup>                       |
| Items supplied           | Mounting nut, steel, nickel-plated (2 x) |

<sup>1)</sup> According to EN 60529.

MECHANICS/ELECTRONICS

|                                |                     |
|--------------------------------|---------------------|
| Supply voltage                 | 10 V DC ... 30 V DC |
| Ripple                         | ≤ 10 %              |
| Voltage drop                   | ≤ 2 V <sup>1)</sup> |
| Time delay before availability | ≤ 100 ms            |

<sup>1)</sup> At  $I_a$  max.

<sup>2)</sup> Supply voltage  $U_a$  and constant ambient temperature  $T_a$ .

<sup>3)</sup> Of  $S_r$ .

|                                        |                                           |
|----------------------------------------|-------------------------------------------|
| Hysteresis                             | 5 % ... 15 %                              |
| Reproducibility                        | $\leq 2\%$ <sup>2)</sup><br><sup>3)</sup> |
| Temperature drift (of S <sub>r</sub> ) | $\pm 10\%$                                |
| EMC                                    | According to EN 60947-5-2                 |
| Continuous current I <sub>a</sub>      | $\leq 200\text{ mA}$                      |
| No load current                        | $\leq 10\text{ mA}$                       |
| Short-circuit protection               | ✓                                         |
| Power-up pulse protection              | ✓                                         |
| Shock and vibration resistance         | 30 g, 11 ms/10 Hz ... 55 Hz, 1 mm         |
| Ambient operating temperature          | -25 °C ... +75 °C                         |
| Housing material                       | Brass, nickel-plated                      |
| Sensing face material                  | Plastic, PA 66                            |
| Housing length                         | 41 mm                                     |
| Thread length                          | 21 mm                                     |
| Tightening torque, max.                | $\leq 5\text{ Nm}$                        |
| UL File No.                            | NRKH.E181493                              |

<sup>1)</sup> At I<sub>a</sub> max.

<sup>2)</sup> Supply voltage U<sub>s</sub> and constant ambient temperature T<sub>a</sub>.

<sup>3)</sup> Of S<sub>r</sub>.

## SAFETY-RELATED PARAMETERS

|                   |             |
|-------------------|-------------|
| MTTF <sub>D</sub> | 1,735 years |
| DC <sub>avg</sub> | 0 %         |

## REDUCTION FACTORS

|                            |                                                |
|----------------------------|------------------------------------------------|
| Note                       | The values are reference values which may vary |
| St37 steel (Fe)            | 1                                              |
| Stainless steel (V2A, 304) | Approx. 0.8                                    |
| Aluminum (Al)              | Approx. 0.45                                   |
| Copper (Cu)                | Approx. 0.4                                    |
| Brass (Br)                 | Approx. 0.4                                    |

## INSTALLATION NOTE


|        |                                            |
|--------|--------------------------------------------|
| Remark | Associated graphic see "Installation note" |
| A      | 8 mm                                       |
| B      | 18 mm                                      |
| C      | 8 mm                                       |
| D      | 12 mm                                      |
| E      | 8 mm                                       |
| F      | 32 mm                                      |

## CERTIFICATES


|                                |   |
|--------------------------------|---|
| EU declaration of conformity   | ✓ |
| UK declaration of conformity   | ✓ |
| ACMA declaration of conformity | ✓ |

|                                                      |   |
|------------------------------------------------------|---|
| Moroccan declaration of conformity                   | ✓ |
| China RoHS                                           | ✓ |
| China Compulsory Product Certification (CCC) ex-empt | ✓ |
| cULus certificate                                    | ✓ |


INSTALLATION NOTE NON-FLUSH INSTALLATION



CONNECTION DIAGRAM CD-004



DIMENSIONAL DRAWING IME08 SHORT-BODY HOUSING, CONNECTOR, NON-FLUSH



- Dimensions in mm (inch)
- ① Connection
  - ② Display LED
  - ③ Fastening nuts (2x); width across 13, metal

Further information as well as suitable accessories, example applications and downloads such as CAD dimensional models, operating instructions and software can be found at [www.sick.com/1040889](http://www.sick.com/1040889)



SICK AG  
WALDKIRCH  
GERMANY  
SICK.COM

# SICK AT A GLANCE

SICK is a leading global technology company for intelligent sensors and integrated solutions in industrial automation. Our technologies set benchmarks, making your industrial processes more efficient, safer and more sustainable – both in logistics and manufacturing operations.

SICK combines sensor intelligence with industry expertise and certified consulting services. We provide the ideal foundation for scalable as well as tailor-made automation solutions and create added value along the entire value chain. Our close partnerships with our customers are more than just a promise: Together, we optimize productivity, improve quality, protect health and safety, and help build a sustainable future. All with empathy and trust.

Since 1946, we have been developing innovative technologies with passion and a pioneering spirit. With a global network in around 40 countries, SICK has a global presence and is always close by. The company's headquarters are located in Waldkirch near Freiburg, Germany. Our customers benefit from our understanding of both local and global requirements, which enables us to deliver tailor-made solutions

**SICK**  
Sensor Intelligence