

CERTIFICATE

No. U6 110756 0147 Rev. 00

Holder of Certificate: **OPPLE Lighting Co., Ltd.**
Room 411, Building 1 No.6111, Longdong Avenue
Pudong New District
201201 Shanghai City
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Multifunctional luminaires
(LED Panel)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142250307701

Date, 2025-08-18


(Michael Xu)

CERTIFICATE

No. U6 110756 0147 Rev. 00

Model(s):

LED SPL-RC-B4 RE295-34W-PL,
LED SPL-RC-B4 RE295-34W-U19-PL,
LED SPL-RC-B4 SQ595-34W-CS-PL,
LED SPL-RC-B4 SQ595-34W-CS-U19-PL,
LED SPL-RC-B4 SQ595-34W-PL,
LED SPL-RC-B4 SQ595-34W-U19-PL,
LED SPL-RC-B4 SQ620-34W-CS-PL,
LED SPL-RC-B4 SQ620-34W-CS-U19-PL,
LED SPL-RC-B4 SQ620-34W-PL,
LED SPL-RC-B4 SQ620-34W-U19-PL,
LED SPL-RC-P7 RE295-29W-TW-U19-PL,
LED SPL-RC-P7 RE295-29W-U19-PL,
LED SPL-RC-P7 SQ595-29W-CS-U19-PL,
LED SPL-RC-P7 SQ595-29W-TW-U19-PL,
LED SPL-RC-P7 SQ595-29W-U19-PL,
LED SPL-RC-P7 SQ620-29W-CS-U19-PL,
LED SPL-RC-P7 SQ620-29W-PL,
LED SPL-RC-P7 SQ620-29W-TW-U19-PL,
LED SPL-RC-P7 SQ620-29W-U19-PL

Brand Name:

OPPLE

Parameters:

Rated voltage:	DC 31-35V
Uout:	59Vdc
Rated current:	See model list
Rated power:	See model list
Protection class:	III
Degree of protection:	For 29W series models: IP54 for exposed part, IP40 for recessed part. For 34W series models: IP40 for whole luminaire.
Blue light risk group:	RG0
ta:	45°C

**Tested
according to:**

EN IEC 60598-1:2021/A11:2022
EN IEC 60598-2-2:2024
EN IEC 60598-2-1:2021

**Production
Facility(ies):**

131858, 086832

CERTIFICATE

No. U6 110756 0147 Rev. 00

Model list:

Model name	Rated current	Rated power (Max)	CCT	Dimension (mm)
LED SPL-RC-B4 RE295-34W-PL	0.95/0.85/0.75/0.65A	34W	3000K/4000K	295×1195×35
LED SPL-RC-B4 RE295-34W-U19-PL	0.95/0.85/0.75/0.65A	34W	3000K/4000K	295×1195×35
LED SPL-RC-B4 SQ595-34W-CS-PL	0.95/0.85/0.75/0.65A	34W	3000K	595×595×35
LED SPL-RC-B4 SQ595-34W-CS-U19-PL	0.95/0.85/0.75/0.65A	34W	4000K	595×595×35
LED SPL-RC-B4 SQ595-34W-PL	0.95/0.85/0.75/0.65A	34W	3000K/4000K	595×595×35
LED SPL-RC-B4 SQ595-34W-U19-PL	0.95/0.85/0.75/0.65A	34W	3000K/4000K	595×595×35
LED SPL-RC-B4 SQ620-34W-CS-PL	0.95/0.85/0.75/0.65A	34W	3000K	620×620×35
LED SPL-RC-B4 SQ620-34W-CS-U19-PL	0.95/0.85/0.75/0.65A	34W	4000K	620×620×35
LED SPL-RC-B4 SQ620-34W-PL	0.95/0.85/0.75/0.65A	34W	3000K/4000K	620×620×35
LED SPL-RC-B4 SQ620-34W-U19-PL	0.95A	34W	3000K/4000K	620×620×35
LED SPL-RC-P7 RE295-29W-TW-U19-PL	0.85A	29W	2700-6500K	295×1195×35
LED SPL-RC-P7 RE295-29W-U19-PL	0.85/0.75/0.65A	29W	3000K/4000K	295×1195×35
LED SPL-RC-P7 SQ595-29W-CS-U19-PL	0.85/0.75/0.65A	29W	3000K/4000K	595×595×35
LED SPL-RC-P7 SQ595-29W-TW-U19-PL	0.85A	29W	2700-6500K	595×595×35
LED SPL-RC-P7 SQ595-29W-U19-PL	0.85/0.75/0.65A	29W	3000K/4000K	595×595×35
LED SPL-RC-P7 SQ620-29W-CS-U19-PL	0.85/0.75/0.65A	29W	3000K/4000K	620×620×35
LED SPL-RC-P7 SQ620-29W-PL	0.85/0.75/0.65A	29W	6500K	620×620×35
LED SPL-RC-P7 SQ620-29W-TW-U19-PL	0.85A	29W	2700-6500K	620×620×35
LED SPL-RC-P7 SQ620-29W-U19-PL	0.85/0.75/0.65A	29W	3000K/4000K	620×620×35