Product data sheet



DX3 LEGRAND

Stop and go automatic resetting for DX³ - 230 V~ - standard - 2 mod.

REF. 406288 | EAN. 3245064062886

STOP&GO is used in the event of unwanted tripping generated by temporarily electrical disturbances or other external events

> The product details page

Peamine kirjeldus:

STOP&GO is used in the event of unwanted tripping generated by temporarily electrical disturbances or other external events

Toote omadused:

- For automatic resetting of 1 module per pole RCCBs and RCBOs up to 63 A
- Can take one control auxiliary and one signalling auxiliary
- No tool required for assemblingAutomatic resetting function
- Control voltage : 230 V~
- Number of modules : 2

Soovitus / piirang

- The signalling auxiliary must be placed between the STOP&GO and the control auxiliary

Dokumentatsioon

Tehniline dokumentatsioon

→ LE04414AB.pdf | PDF (3.04Mo)

→ F01284EN-01.pdf | PDF (0.99Mo)

CAD & Disaini spetsifikatsioonid / BIM

→ 406288.dwg | DWG (0.16Mo)

Regulated Substances Compliance

RoHS Certificate of Compliance | PDF

Manufacturer REACH Declaration | PDF

Lepingud ja sertifikaadid

→ LGRP-00509-V01.01-EN.pdf | PDF (0.95Mo)