OMRON Industrial Automation



R88M-C6L1K530T-OS2-GS

C6 AC servo motor, Low inertia, 1.5 kW, 230 VAC, 3000 rpm, 4.8 Nm, absolute encoder, with oil seal and key

Specifications

Servo control method	EtherCAT
Drive supply voltage	230 V single phase, 230 V three phase
Rated output	1.5 kW
Rated speed	3000 r/min
Rated torque	4.8 Nm
Peak torque	14.7 Nm
Encoder type	Absolute with battery
Encoder resolution	26 Bit
Motor with brake	✖
Motor with oil seal	✔
Flange size square (LC)	100 mm
Shaft diameter	22 mm
Shaft with key	✔
Shaft with tap	✔
Product Weight (unpacked)	4500 g

Fits to



R88D-C6N15H-ECT-GS
C6 AC servo drive, Standard model, EtherCAT Communications, 1.5 kW, 1/3-phase, 230 VAC

Accessories

R88A-CACE001-5SF-IE	C6 series servo motor power cable, 1.5 m, non braked, 230V: 1.3 kW & 1.5 kW (3000rpm), 400V: 3 kW, 4 kW & 5 kW
R88A-CACE003SF-IE	C6 series servo motor power cable, 3 m, non braked, 230V: 1.3 kW & 1.5 kW (3000rpm), 400V: 3 kW, 4 kW & 5 kW
R88A-CACE005SF-IE	C6 series servo motor power cable, 5 m, non braked, 230V: 1.3 kW & 1.5 kW (3000rpm), 400V: 3 kW, 4 kW & 5 kW
R88A-CACE010SF-IE	C6 series servo motor power cable, 10 m, non braked, 230V: 1.3 kW & 1.5 kW (3000rpm), 400V: 3 kW, 4 kW & 5 kW
R88A-CACE015SF-IE	C6 series servo motor power cable, 15 m, non braked, 230V: 1.3 kW & 1.5 kW (3000rpm), 400V: 3 kW, 4 kW & 5 kW
R88A-CACE020SF-IE	C6 series servo motor power cable, 20 m, non braked, 230V: 1.3 kW & 1.5 kW (3000rpm), 400V: 3 kW, 4 kW & 5 kW
R88A-CRCB001-5NF-BS-IE	C6 series servo encoder cable, with battery, 1.5 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW

R88A-CRCB001-5NF-IE	C6 series servo encoder cable, 1.5 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB003NF-BS-IE	C6 series servo encoder cable, with battery, 3 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB003NF-IE	C6 series servo encoder cable, 3 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB005NF-BS-IE	C6 series servo encoder cable, with battery, 5 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB005NF-IE	C6 series servo encoder cable, 5 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB010NF-BS-IE	C6 series servo encoder cable, with battery, 10 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB010NF-IE	C6 series servo encoder cable, 10 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB015NF-BS-IE	C6 series servo encoder cable, with battery, 15 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB015NF-IE	C6 series servo encoder cable, 15 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB020NF-BS-IE	C6 series servo encoder cable, with battery, 20 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW
R88A-CRCB020NF-IE	C6 series servo encoder cable, 20 m, 230V: 850W to 1.5kW (100 & 130 mm flange), 400V: 850 W to 7.5 kW

Downloads

CAD file



C6 Series
Brochure

EN PDF 3.44 MB



C6 Series
Users Manual

EN PDF 41.9 MB



C6 Series Servo System
Datasheet

EN PDF 7 MB



Motor Sizing Tool
Operation Manual

EN PDF 4.67 MB



Motor Sizing Tool V1.91.1.1
Configurator

EN ZIP 213 MB



R88M-C6-GS
Eu declaration of conformity

EN PDF 292 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 24 November, 2026. Click here for terms of use.